



- NOTES: 1.) MATERIAL - 316 SST
 2.) ALL BREAKS TO BE SHARP & @ 90°.
 3.) ALL WELDS TO BE FULL PENETRATION AND CONTINUOUS FILLET WELD UNLESS OTHERWISE NOTED.
 4.) DEBURR OR BREAK SHARP EDGES / CORNERS.

ITEM	QTY	REFERENCE	ITEM SIZE/DESCRIPTION	MATERIAL	WT.(LBS) (TOTAL)
H	1	*****	#7 GA. SHIT. x 11" x 122"	316 SST	72.7
G	1	*****	#7 GA. SHIT. x 5" x 55"	316 SST	17.3
F	1	*****	#7 GA. SHIT. x 5" x 55"	316 SST	17.3
E	12	*****	3/8-16UNC x1" HEX W/LW & HN	316 SST	0.7
D	6	*****	VIBRATION ISOLATOR (TYPE R-1)	*****	2.3
C	4	NO DETAIL	#7 GA. SHIT. x 2" x 6"	316 SST	0.8
B	3	*****	#7 GA. SHIT. x 5" x 55"	316 SST	16.4
A	1	*****	#7 GA. SHIT. x 11" x 122"	316 SST	72.7
TOTAL					199.8

FILE: /42988/42988-11.dwg	PLOT: 31/75/20/75	ORIGIN: 0,0	FACTOR: 1=8	ANGULAR	SCALE: 1/2"=1'-0"	SIZE: D	DRAWING NUMBER: 42988-11	REV.
DRAWN: AHH 05-22-02				CHECKED:		APPROVED:		
TOLERANCES: ±1/4"				CUSTOMER:		JOB NO. 10B		
FRACTIONAL: .XX				TITLE: SKID ASSEMBLY				
REVISION				DATE		DWN		CHK'D/APP'D
DESCRIPTION				ITEM H				